


### Light efficiency:



### Light quality:



### Color temperature:



**Output: 373 lm**

**Peak: 157 cd**

**Power: 12,0 W**

**PF: 1,0**



### Product name:

**Pegasus-3-Gold-0508-822-CSG**

### Item number:

**FLNP-L-16A-0508-822-CSG**

### Date and time:

**17.03.2021 16:58:07**

### Description:

**Rank: M1A4T**

**Toleranzen:**

**Lumen +/-4%**

**Candela +/-2,5%**

**Colour Temp +/-35 Grad K**

**CRI +/-0,7**

**Angular Resolution 1 Grad step**


**Last Calibration 20-05-2020**

**Pruefer: Peter Ulrich**

**Pruefort: Lichtlabor**


**Gaustrasse13-15**

**55411 Bingen am Rhein**






**CIE 1931**  
**x: 0,503**  
**y: 0,411**

### Spectra




### Power






**TM30: 87,0**



**CRI: 84,6 (R1-R8)**



**CRI R values, only R1-R8 are used to calculate final CRI value**

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
84,7	96,0	90,9	81,9	85,6	96,9	80,3	60,6	23,7	92,1	82,8	89,4	87,6	95,8	76,9


**TM30 C values, 16 binned values out of total of 99 C values**

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
81,1	83,2	81,7	93,4	95,3	92,6	89,8	94,0	88,6	86,8	88,6	90,0	87,5	68,0	87,3	78,4

**CQS Q values**

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
75,4	86,3	85,7	80,7	80,9	81,8	80,7	80,8	86,5	87,9	84,1	80,1	78,5	73,2	73,5

**CQS: 80,2**



## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2196 K	84,6	23,7	87,0	95,9	80,2	0,503	0,411	0,291	0,356	-0,0013







## Rf 87,0


Fidelity index Rf

## Rg 95,9

Gamut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	81	-10%	2%
2	83	-7%	7%
3	82	-2%	9%
4	93	-1%	3%
5	95	1%	2%
6	93	1%	-1%
7	90	-5%	-4%
8	94	-4%	1%
9	89	-4%	5%
10	87	-2%	8%
11	89	3%	7%
12	90	5%	1%
13	87	4%	-13%
14	68	-1%	-22%
15	87	-4%	-8%
16	78	-11%	-12%





## Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
157lx	39lx	17lx	10lx	6lx	4lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx
14,5fcd	3,6fcd	1,6fcd	0,9fcd	0,6fcd	0,4fcd	0,3fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd	0fcd

## Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
157	156	152	146	137	126	114	103	91	80	70	61	51	43	34	27	20	15	6	0
100%	99%	97%	93%	87%	81%	73%	66%	58%	51%	45%	39%	33%	27%	22%	17%	13%	9%	4%	0%

## Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
157	156	152	146	139	129	121	108	92	79	66	54	43	33	24	16	9	4	1	1
100%	99%	97%	94%	89%	82%	77%	69%	59%	50%	42%	35%	27%	21%	15%	10%	6%	2%	0%	0%

## Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
157	156	152	146	137	126	114	103	91	80	70	61	51	43	34	27	20	15	6	0
100%	99%	97%	93%	87%	81%	73%	66%	58%	51%	45%	39%	33%	27%	22%	17%	13%	9%	4%	0%

## Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
157	156	152	146	139	129	121	108	92	79	66	54	43	33	24	16	9	4	1	1
100%	99%	97%	94%	89%	82%	77%	69%	59%	50%	42%	35%	27%	21%	15%	10%	6%	2%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
91,5°	160,1°	201,1°	78,8%	57,0%

### ISO candela diagram




10%	16 cd
20%	31 cd
30%	47 cd
40%	63 cd
50%	78 cd
60%	94 cd
70%	110 cd
80%	125 cd
90%	141 cd

#### Conditions:

Number of c-planes: 16

Candela at center: 157 cd

### ISO lux diagram



3%	47,0m lx
5%	78,3m lx
10%	0,157 lx
30%	0,470 lx
50%	0,783 lx

#### Conditions:

Number of c-planes: 16

Lux at center: 1,57 lx

*Lux distribution on a surface  
when lamp is mounted at 10  
meters from the surface.*

### Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X      Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18,3	19,5	18,6	19,8	20,0	18,8	20,0	19,1	20,3	20,5
	3H	19,6	20,8	20,0	21,1	21,3	19,9	21,1	20,3	21,4	21,6
	4H	20,1	21,3	20,5	21,6	21,8	20,3	21,5	20,7	21,8	22,0
	6H	20,7	21,7	21,0	22,0	22,3	20,7	21,7	21,0	22,0	22,4
	8H	20,8	21,8	21,2	22,1	22,6	20,8	21,8	21,1	22,1	22,5
	12H	21,0	21,9	21,3	22,3	22,7	20,8	21,8	21,2	22,1	22,5
4H	2H	18,8	20,0	19,2	20,3	20,5	19,2	20,4	19,6	20,6	20,9
	3H	20,4	21,3	20,7	21,7	22,1	20,6	21,5	20,9	21,9	22,3
	4H	21,0	21,9	21,4	22,3	22,8	21,0	21,9	21,5	22,4	22,9
	6H	21,6	22,4	22,1	22,8	23,2	21,4	22,3	21,9	22,7	23,0
	8H	21,8	22,6	22,3	23,0	23,4	21,6	22,4	22,1	22,7	23,1
	12H	22,0	22,7	22,5	23,1	23,6	21,6	22,3	22,1	22,7	23,2
8H	4H	21,2	22,0	21,7	22,4	22,7	21,3	22,0	21,8	22,4	22,8
	6H	22,0	22,6	22,5	23,0	23,6	21,8	22,4	22,3	22,9	23,4
	8H	22,3	22,9	22,9	23,4	24,0	22,0	22,5	22,5	23,1	23,7
	12H	22,7	23,1	23,3	23,6	24,2	22,1	22,6	22,7	23,1	23,7
12H	4H	21,2	21,9	21,7	22,3	22,8	21,3	21,9	21,8	22,3	22,8
	6H	22,0	22,6	22,6	23,1	23,7	21,9	22,4	22,4	22,9	23,6
	8H	22,4	22,9	23,0	23,4	24,0	22,1	22,5	22,7	23,1	23,7
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,1 / -0,1				
S = 1.5H		0,2 / -0,3					0,3 / -0,5				
S = 2.0H		0,4 / -0,6					0,8 / -0,9				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 373 lm total luminous flux											

## Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	104	99	95	105	101	97	94	97	93	90	92	90	87	88	86	84	82
2	99	91	84	79	96	89	83	77	85	80	75	81	77	73	78	75	71	69
3	91	80	72	66	88	79	71	65	75	69	64	72	67	63	70	65	61	59
4	83	72	63	57	81	70	62	56	67	61	55	65	59	54	63	57	53	51
5	77	64	56	49	75	63	55	49	61	54	48	59	52	47	57	51	47	45
6	71	58	50	43	69	57	49	43	55	48	42	53	47	42	52	46	41	39
7	66	53	45	39	64	52	44	38	50	43	38	49	42	38	47	42	37	35
8	62	49	40	35	60	48	40	34	46	39	34	45	39	34	44	38	34	32
9	58	45	37	31	56	44	36	31	43	36	31	42	35	31	41	35	30	29
10	54	41	34	29	53	41	33	28	40	33	28	39	32	28	38	32	28	26

LAMPS (number of lamps)


Luminaire budgetary diagram



## Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
14,7 lm	41,0 lm	58,8 lm	65,8 lm	62,0 lm	51,5 lm	38,0 lm	23,5 lm	10,9 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
2,47 lm	1,00 lm	0,813 lm	0,735 lm	0,605 lm	0,469 lm	0,345 lm	0,212 lm	0,071 lm

### Warmup curve



### Warmup result

Warmup time:	17 min 47 sec
Warmup variation	-4,3%

### Warmup conditions

Stable period:	15 min
Stable change max:	2,0%
Minimum time:	15 min

### Color temperature change

CCT start	CCT change	CCT end
2199 K	-3 K	2196 K

### Output change

Output start	Output change	Output end
387 lm	-14 lm	373 lm