

Light efficiency:

128 Lumen/Watt

Light quality:

CRI: 0,0

Color temperature:

0 K

Output: 982 lm

Peak: 467 cd

Power: 7,7 W

PF: 1,0



Product name:

Defiant-0508-XXG-L6F

Item number:

FLNP/L22A0508/XXG/L6F

Date and time:

07.07.2020 15:20:41

Description:

Rank: R2G2B4/RC2GA2BA5/A

Toleranzen:

Lumen +/-4%

Candela +/-2,5%

Colour Temp +/-35 K

CRI +/-0,7

Angular Resolution 1 Grad Step

Last Calibration 20.05.2020

Pruefer:


Peter Ulrich

Pruefort:

Lichtlabor

Gaustrasse 13

55411 Bingen am Rhein




CIE 1931


x: 0,200



y: 0,732

Spectra



Power





TM30: 0,0

CRI: 0,0 (R1-R8)

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	

CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS: 0,0

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0,0	0,0	0,0	0,0	0,0	0,200	0,732	0,070	0,386	n/a





Rf 0,0


Fidelity index Rf

Rg 0,0

Gammut index Rg

		Graphic shifts (%)	
Hue Bin	R _f	Chroma	Hue
1	0	0%	0%
2	0	0%	0%
3	0	0%	0%
4	0	0%	0%
5	0	0%	0%
6	0	0%	0%
7	0	0%	0%
8	0	0%	0%
9	0	0%	0%
10	0	0%	0%
11	0	0%	0%
12	0	0%	0%
13	0	0%	0%
14	0	0%	0%
15	0	0%	0%
16	0	0%	0%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
450lx	113lx	50lx	28lx	18lx	13lx	9lx	7lx	6lx	5lx	4lx	3lx	3lx	2lx	2lx	2lx	2lx	1lx	1lx	1lx
41,8fcd	10,5fcd	4,6fcd	2,6fcd	1,7fcd	1,2fcd	0,9fcd	0,7fcd	0,5fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
450	455	460	467	460	406	327	235	144	89	59	50	58	55	52	40	26	16	6	0
100%	101%	102%	104%	102%	90%	73%	52%	32%	20%	13%	11%	13%	12%	11%	9%	6%	4%	1%	0%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
450	448	446	441	435	426	416	403	388	369	343	300	237	173	114	70	36	14	1	1
100%	99%	99%	98%	97%	95%	92%	89%	86%	82%	76%	67%	53%	38%	25%	16%	8%	3%	0%	0%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
450	455	460	467	460	406	327	235	144	89	59	50	58	55	52	40	26	16	6	0
100%	101%	102%	104%	102%	90%	73%	52%	32%	20%	13%	11%	13%	12%	11%	9%	6%	4%	1%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
450	448	446	441	435	426	416	403	388	369	343	300	237	173	114	70	36	14	1	1
100%	99%	99%	98%	97%	95%	92%	89%	86%	82%	76%	67%	53%	38%	25%	16%	8%	3%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
87,1°	139°	175°	84,5%	67,6%

ISO candela diagram




10%	45 cd
20%	90 cd
30%	135 cd
40%	180 cd
50%	225 cd
60%	270 cd
70%	315 cd
80%	360 cd
90%	405 cd

Conditions:

Number of c-planes: 16

Candela at center: 450 cd

ISO lux diagram



3%	0,135 lx
5%	0,225 lx
10%	0,450 lx
30%	1,35 lx
50%	2,25 lx

Conditions:

Number of c-planes: 16

Lux at center: 4,50 lx

*Lux distribution on a surface
when lamp is mounted at 10
meters from the surface.*

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	16,8	17,8	17,0	18,1	18,3	24,3	25,3	24,5	25,6	25,8
	3H	18,3	19,4	18,7	19,7	19,8	25,3	26,4	25,7	26,7	26,9
	4H	19,0	20,1	19,4	20,3	20,6	25,8	26,8	26,2	27,1	27,3
	6H	19,5	20,5	19,8	20,7	21,1	26,1	27,0	26,4	27,3	27,7
	8H	19,7	20,6	20,0	20,9	21,3	26,2	27,1	26,5	27,4	27,8
	12H	19,8	20,6	20,1	21,0	21,4	26,2	27,1	26,6	27,4	27,9
4H	2H	17,3	18,4	17,7	18,6	18,9	24,0	25,1	24,4	25,4	25,6
	3H	19,2	20,1	19,6	20,4	20,9	25,3	26,2	25,7	26,5	27,0
	4H	20,0	20,8	20,4	21,2	21,8	25,7	26,5	26,2	26,9	27,5
	6H	20,6	21,4	21,1	21,7	22,1	26,1	26,9	26,6	27,2	27,6
	8H	20,8	21,5	21,3	21,9	22,2	26,2	26,9	26,7	27,3	27,7
	12H	20,9	21,5	21,4	21,9	22,4	26,3	26,9	26,8	27,3	27,8
8H	4H	20,4	21,1	20,9	21,4	21,8	25,7	26,4	26,2	26,8	27,1
	6H	21,1	21,6	21,6	22,1	22,7	26,1	26,7	26,7	27,1	27,7
	8H	21,4	21,9	21,9	22,4	23,0	26,4	26,8	26,9	27,3	28,0
	12H	21,6	22,0	22,2	22,5	23,1	26,5	26,9	27,1	27,4	28,0
12H	4H	20,4	21,0	20,9	21,4	21,9	25,7	26,2	26,2	26,7	27,1
	6H	21,2	21,7	21,8	22,2	22,9	26,2	26,6	26,7	27,1	27,8
	8H	21,6	22,0	22,1	22,5	23,1	26,4	26,7	26,9	27,2	27,9
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,6 / -0,4					0,5 / -0,7				
S = 1.5H		1,1 / -0,5					1,5 / -1,9				
S = 2.0H		1,7 / -0,6					2,7 / -3,0				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 982 lm total luminous flux											

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	110	105	102	98	107	103	99	96	98	95	93	94	92	90	90	88	87	85
2	101	94	88	83	98	92	86	82	88	83	79	84	81	77	81	78	75	73
3	93	84	77	71	91	82	76	70	79	74	69	76	71	67	73	69	66	64
4	86	76	68	62	84	74	67	61	72	65	60	69	64	59	67	62	58	56
5	80	69	61	55	78	68	60	54	65	59	54	63	57	53	61	56	52	50
6	75	63	55	49	73	62	54	49	60	53	48	58	52	47	56	51	47	45
7	70	57	49	44	68	57	49	44	55	48	43	53	47	43	52	46	42	41
8	65	53	45	40	64	52	45	40	51	44	39	49	43	39	48	43	39	37
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	39	35	34
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	36	32	31

LAMPS (number of lamps)


Luminaire budgetary diagram



Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
43,1 lm	129 lm	200 lm	208 lm	151 lm	98,3 lm	68,2 lm	43,9 lm	18,3 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
5,10 lm	4,76 lm	3,12 lm	2,60 lm	2,20 lm	1,75 lm	1,29 lm	0,789 lm	0,266 lm

Warmup curve



Warmup result

Warmup time:	15 min 2 sec
Warmup variation	-1,1%

Warmup conditions

Stable period:	15 min
Stable change max:	2,0%
Minimum time:	15 min

Color temperature change

CCT start	CCT change	CCT end
0 K	0 K	0 K

Output change

Output start	Output change	Output end
991 lm	-9 lm	982 lm