

Light efficiency:

115 Lumen/Watt

Light quality:

CRI: 0,0

Color temperature:



0 K

Output: 880 lm

Peak: 335 cd


Power: 7,7 W

PF: 1,0




CIE 1931
x: 0,199
y: 0,731

Spectra



Power



Product name:

Defiant-0508-XXG-CFF

Item number:

FLNP/L22A0508/XXG/CFF

Date and time:

06.07.2020 11:49:25

Description:

Rank: R2G2B4/RC2GA2BA5/A

Toleranzen:

Lumen +/-4%

Candela +/-2,5%

Colour Temp +/-35 K

CRI +/-0,7

Angular Resolution 1 Grad Step

Last Calibration 20.05.2020

Pruefer:



Peter Ulrich

Pruefort:

Lichtlabor

Gaustrasse 13

55411 Bingen am Rhein



TM30: 0,0

CRI: 0,0 (R1-R8)

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	

CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS: 0,0

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15	

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0,0	0,0	0,0	0,0	0,0	0,199	0,731	0,070	0,386	n/a






Rf 0,0


Fidelity index Rf

Rg 0,0

Gammut index Rg

		Graphic shifts (%)	
Hue Bin	R _f	Chroma	Hue
1	0	0%	0%
2	0	0%	0%
3	0	0%	0%
4	0	0%	0%
5	0	0%	0%
6	0	0%	0%
7	0	0%	0%
8	0	0%	0%
9	0	0%	0%
10	0	0%	0%
11	0	0%	0%
12	0	0%	0%
13	0	0%	0%
14	0	0%	0%
15	0	0%	0%
16	0	0%	0%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
334lx	84lx	37lx	21lx	13lx	9lx	7lx	5lx	4lx	3lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx
31,1fcd	7,8fcd	3,5fcd	1,9fcd	1,2fcd	0,9fcd	0,6fcd	0,5fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
334	332	328	319	307	291	272	250	223	195	165	136	109	84	63	45	31	21	9	0
100%	99%	98%	95%	92%	87%	81%	75%	67%	58%	49%	41%	33%	25%	19%	13%	9%	6%	3%	0%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
334	333	329	322	311	298	282	261	238	212	183	152	122	93	68	45	26	12	2	2
100%	100%	98%	96%	93%	89%	84%	78%	71%	63%	55%	46%	36%	28%	20%	14%	8%	4%	1%	0%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
334	332	328	319	307	291	272	250	223	195	165	136	109	84	63	45	31	21	9	0
100%	99%	98%	95%	92%	87%	81%	75%	67%	58%	49%	41%	33%	25%	19%	13%	9%	6%	3%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
334	333	329	322	311	298	282	261	238	212	183	152	122	93	68	45	26	12	2	2
100%	100%	98%	96%	93%	89%	84%	78%	71%	63%	55%	46%	36%	28%	20%	14%	8%	4%	1%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
102,4°	158°	177,9°	80,0%	56,6%

ISO candela diagram




10%	33 cd
20%	67 cd
30%	100 cd
40%	134 cd
50%	167 cd
60%	201 cd
70%	234 cd
80%	267 cd
90%	301 cd

Conditions:

Number of c-planes: 16

Candela at center: 334 cd

ISO lux diagram



Mounting height: 10 meters (33 feet)

3%	0,100 lx
5%	0,167 lx
10%	0,334 lx
30%	1,00 lx
50%	1,67 lx

Conditions:

Number of c-planes: 16

Lux at center: 3,34 lx

*Lux distribution on a surface
when lamp is mounted at 10
meters from the surface.*

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	22,0	23,2	22,3	23,5	23,7	23,1	24,2	23,3	24,5	24,8
	3H	23,0	24,2	23,4	24,5	24,7	24,2	25,4	24,6	25,7	25,9
	4H	23,4	24,6	23,8	24,8	25,1	24,7	25,8	25,1	26,1	26,4
	6H	23,8	24,8	24,1	25,1	25,4	25,1	26,1	25,4	26,4	26,7
	8H	23,9	24,9	24,2	25,2	25,6	25,2	26,2	25,5	26,5	26,9
	12H	24,0	24,9	24,3	25,3	25,7	25,2	26,2	25,6	26,5	27,0
4H	2H	22,6	23,7	23,0	24,0	24,3	23,4	24,5	23,8	24,8	25,1
	3H	23,8	24,8	24,2	25,1	25,6	24,8	25,8	25,2	26,1	26,6
	4H	24,2	25,1	24,7	25,6	26,1	25,4	26,2	25,8	26,7	27,2
	6H	24,7	25,5	25,2	25,9	26,3	25,8	26,7	26,3	27,0	27,4
	8H	24,8	25,6	25,3	26,0	26,4	26,0	26,7	26,5	27,1	27,5
	12H	25,0	25,6	25,5	26,1	26,5	26,1	26,7	26,6	27,1	27,6
8H	4H	24,5	25,3	25,0	25,6	26,0	25,5	26,3	26,0	26,6	27,0
	6H	25,1	25,7	25,6	26,1	26,7	26,1	26,7	26,6	27,1	27,7
	8H	25,4	25,9	25,9	26,4	27,0	26,4	26,9	26,9	27,4	28,0
	12H	25,6	26,0	26,2	26,5	27,1	26,5	27,0	27,1	27,5	28,1
12H	4H	24,5	25,2	25,0	25,6	26,1	25,5	26,1	26,0	26,6	27,0
	6H	25,2	25,7	25,7	26,2	26,8	26,2	26,7	26,7	27,2	27,8
	8H	25,4	25,9	26,0	26,4	27,0	26,4	26,9	27,0	27,4	28,0
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,2					0,1 / -0,1				
S = 1.5H		0,3 / -0,5					0,2 / -0,4				
S = 2.0H		0,7 / -0,9					0,7 / -0,8				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 880 lm total luminous flux											

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	109	104	100	96	106	101	98	94	97	94	91	93	90	88	89	87	85	83
2	99	91	85	79	96	89	83	78	85	80	76	82	77	74	78	75	72	70
3	91	80	73	66	88	79	71	66	76	69	64	73	67	63	70	65	61	59
4	83	72	63	57	81	70	62	56	67	61	55	65	59	54	63	57	53	51
5	77	64	55	49	75	63	55	49	61	53	48	58	52	47	56	51	47	44
6	71	58	49	43	69	57	49	43	55	48	42	53	47	42	51	46	41	39
7	66	53	44	38	64	52	44	38	50	43	37	48	42	37	47	41	37	35
8	61	48	40	34	60	47	39	34	46	39	34	45	38	33	43	37	33	31
9	57	44	36	31	56	44	36	31	42	35	30	41	35	30	40	34	30	28
10	54	41	33	28	53	40	33	28	39	32	28	38	32	27	37	31	27	25

LAMPS (number of lamps)


Luminaire budgetary diagram



Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
31,6 lm	90,3 lm	136 lm	160 lm	157 lm	129 lm	89,1 lm	49,7 lm	19,9 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
4,85 lm	2,79 lm	2,46 lm	2,23 lm	1,83 lm	1,42 lm	1,05 lm	0,641 lm	0,216 lm

Warmup curve



Warmup result

Warmup time:	15 min 2 sec
Warmup variation	-1,3%

Warmup conditions

Stable period:	15 min
Stable change max:	2,0%
Minimum time:	15 min

Color temperature change

CCT start	CCT change	CCT end
0 K	0 K	0 K

Output change

Output start	Output change	Output end
888 lm	-9 lm	880 lm