Light efficiency:

115 Lumen/Watt

Light quality:


CRI: 95,0


Color temperature:

2700 K

Output: 275 lm
Peak: 418 cd

Power: 2,4 W
PF: 1,0





Product name:
Sta-Maria-6_510mm_927_Lens-15°-Frosted


Item number:
NP/L1C/01E/0510/927/L1F

Date and time:
29.06.2022 12:43:11


Description:
Tolerances:
Lumen +/-4%
Candela +/-2,5%
Colour Temp +/-35 Kelvin
CRI +/-0,7
Angular Resolution: 1 Degree Step
Last Calibration 20-09-2021
Tester: Peter Ulrich
Test Site: Lichtlabor
Gaustrasse 13
55411 Bingen am Rhein

CIE 1931
x: 0,460
y: 0,411


Spectra




Power



Color details




CIE 1931




CIE 1931 ZOOM

TM30: 92,6



CRI: 95,0 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
96,0	98,0	98,2	95,6	95,7	96,9	93,2	86,2	70,1	94,3	96,7	83,7	96,8	98,2	92,4


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92,7	93,9	91,6	94,3	94,9	95,5	93,7	98,2	95,3	91,1	89,5	90,1	92,2	89,0	93,4	86,8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
90,3	95,5	89,0	89,3	92,9	93,5	90,6	92,0	97,2	94,1	93,6	93,1	93,0	89,8	89,7

CQS: 91,8



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2700 K	95,0	70,1	92,6	100,4	91,8	0,460	0,411	0,263	0,352	-0,0014

TM30 details


Rf 92,6


Fidelity index Rf


Rg 100,4


Gammut index Rg


		Graphic shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	93	-4%	0%
2	94	-2%	2%
3	92	-1%	4%
4	94	-1%	1%
5	95	0%	2%
6	96	2%	0%
7	94	-2%	-1%
8	98	0%	-1%
9	95	-1%	2%
10	91	0%	6%
11	90	2%	8%
12	90	5%	1%
13	92	3%	-5%
14	89	4%	-8%
15	93	-1%	-3%
16	87	-1%	-10%















Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
411lx	103lx	46lx	26lx	16lx	11lx	8lx	6lx	5lx	4lx	3lx	3lx	2lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx
38,2fcd	9,6fcd	4,2fcd	2,4fcd	1,5fcd	1,1fcd	0,8fcd	0,6fcd	0,5fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
411	396	355	297	234	174	122	84	59	43	33	28	26	25	26	24	22	21	20	21
100%	96%	86%	72%	57%	42%	30%	20%	14%	11%	8%	7%	6%	6%	6%	6%	5%	5%	5%	5%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
411	412	412	414	415	416	417	418	417	416	412	405	396	383	368	350	327	303	277	250
100%	100%	100%	101%	101%	101%	102%	102%	101%	101%	100%	99%	96%	93%	90%	85%	80%	74%	67%	61%

Intensities in 180° c-plane


0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
411	396	355	297	234	174	122	84	59	43	33	28	26	25	26	24	22	21	20	21
100%	96%	86%	72%	57%	42%	30%	20%	14%	11%	8%	7%	6%	6%	6%	6%	5%	5%	5%	5%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
411	412	412	414	415	416	417	418	417	416	412	405	396	383	368	350	327	303	277	250
100%	100%	100%	101%	101%	101%	102%	102%	101%	101%	100%	99%	96%	93%	90%	85%	80%	74%	67%	61%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
36,5°	**68,4°**	**155,4°**	**83,7%**	**69,3%**

ISO candela diagram




10%	41 cd
20%	82 cd
30%	123 cd
40%	164 cd
50%	206 cd
60%	247 cd
70%	288 cd
80%	329 cd
90%	370 cd

Conditions:

Number of c-planes: 16

Candela at center: 411 cd

ISO lux diagram



Mounting height: 10 meters (33 feet)

3%	0,123 lx
5%	0,206 lx
10%	0,411 lx
30%	1,23 lx
50%	2,06 lx

Conditions:

Number of c-planes: 16

Lux at center: 4,11 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	10,8	11,7	10,9	12,0	12,2	18,9	19,8	19,0	20,1	20,3
	3H	13,2	14,2	13,6	14,5	14,6	19,4	20,4	19,8	20,7	20,8
	4H	14,6	15,6	15,0	15,8	16,1	19,6	20,6	20,0	20,8	21,1
	6H	15,9	16,8	16,2	17,1	17,4	19,8	20,7	20,1	21,0	21,3
	8H	16,3	17,1	16,6	17,4	17,8	19,9	20,7	20,2	21,0	21,4
	12H	16,5	17,3	16,8	17,6	18,1	19,9	20,7	20,2	21,0	21,5
4H	2H	11,4	12,4	11,8	12,6	12,9	18,6	19,6	19,0	19,9	20,1
	3H	14,2	15,0	14,5	15,3	15,8	19,4	20,2	19,7	20,5	21,0
	4H	15,7	16,5	16,1	16,9	17,4	19,6	20,3	20,0	20,8	21,3
	6H	17,1	17,9	17,6	18,2	18,6	19,8	20,6	20,3	20,9	21,3
	8H	17,6	18,3	18,1	18,6	19,0	19,9	20,6	20,4	21,0	21,4
	12H	17,8	18,4	18,3	18,8	19,3	20,0	20,6	20,5	21,0	21,5
8H	4H	16,1	16,8	16,6	17,1	17,5	19,6	20,3	20,1	20,7	21,0
	6H	17,8	18,3	18,3	18,8	19,3	20,0	20,5	20,5	20,9	21,5
	8H	18,4	18,9	18,9	19,4	20,0	20,2	20,6	20,7	21,1	21,8
	12H	18,8	19,2	19,4	19,7	20,3	20,3	20,7	20,9	21,2	21,8
12H	4H	16,1	16,7	16,6	17,1	17,6	19,6	20,2	20,1	20,6	21,1
	6H	17,9	18,4	18,4	18,9	19,5	20,1	20,5	20,6	21,0	21,7
	8H	18,6	19,0	19,2	19,5	20,1	20,3	20,7	20,9	21,2	21,8

Variation of the observer position for the luminaire distance S		
S = 1.0H	0,0 / 0,0	1,4 / -1,4
S = 1.5H	0,2 / -0,2	3,0 / -2,2
S = 2.0H	0,4 / -0,3	4,5 / -2,8
Standard table	n/a	n/a
Correction summand	n/a	n/a
Corrected glare indices referring to 275 lm total luminous flux		

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)				Room Values are expressed as percentage of Lumens delivered to the task surface													
0	118	118	118	118	115	115	115	115	110	110	110	104	104	104	100	100	100	97
1	110	105	102	98	107	103	100	97	98	96	93	94	92	90	90	88	87	85
2	102	95	89	84	99	93	88	83	89	85	81	86	82	79	82	79	77	75
3	95	86	79	74	92	84	78	73	81	76	72	78	74	70	76	72	69	67
4	89	79	72	66	86	77	71	65	75	69	64	72	67	63	70	66	62	60
5	83	73	65	60	81	71	64	59	69	63	58	67	62	58	65	61	57	55
6	78	67	60	54	77	66	59	54	64	58	54	63	57	53	61	56	52	51
7	74	63	55	50	72	62	55	50	60	54	49	59	53	49	57	52	49	47
8	70	59	52	47	69	58	51	46	57	50	46	55	50	46	54	49	45	44
9	66	55	48	44	65	54	48	43	53	47	43	52	47	43	51	46	42	41
10	63	52	45	41	62	51	45	41	50	45	40	49	44	40	48	44	40	38

Luminaire budgetary diagram




Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
31,9 lm	53,3 lm	47,0 lm	40,6 lm	33,1 lm	24,3 lm	16,4 lm	13,2 lm	8,17 lm

90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
1,56 lm	1,74 lm	0,550 lm	0,497 lm	0,378 lm	0,276 lm	0,203 lm	0,125 lm	1,75 lm

Warmup curve



Warmup result

Warmup time:	**Lamp stabilized in 15 min 3 sec**
Warmup variation	**-1,2%**

Warmup conditions

Stable period:	**15 min**
Stable change max:	**2,0%**
Minimum time:	**15 min**

Color temperature change

CCT start	CCT change	CCT end
2702 K	-2 K	2700 K

Output change

Output start	Output change	Output end
278 lm	-3 lm	275 lm