

### Light efficiency:

**54 Lumen/Watt**

### Light quality:

**CRI: 0,0**

### Color temperature:


**0 K**

**Output: 417 lm**

**Peak: 135 cd**


**Power: 7,7 W**

**PF: 1,0**




**CIE 1931**  
**x: 0,685**  
**y: 0,301**

### Spectra



### Power



### Product name:

**Defiant-0508-XXR-CST**

### Item number:

**FLNP/L22A0508/XXR/CST**

### Date and time:

**30.06.2020 10:28:00**

### Description:

**Rank: R2G2B4/RC2GA2BA5/A**

**Toleranzen:**

**Lumen +/-4%**

**Candela +/-2,5%**

**Colour Temp +/-35 K**

**CRI +/-0,7**

**Angular Resolution 1 Grad Step**

**Last Calibration 20.05.2020**

**Pruefer:**



**Peter Ulrich**

**Pruefort:**

**Lichtlabor**

**Gaustrasse 13**

**55411 Bingen am Rhein**



TM30: 0,0

CRI: 0,0 (R1-R8)

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	

CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS: 0,0

0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15	

## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
0 K	0,0	0,0	0,0	0,0	0,0	0,685	0,301	0,522	0,344	n/a





## Rf 0,0


Fidelity index Rf

## Rg 0,0

Gammut index Rg

		Graphic shifts (%)	
Hue Bin	R <sub>f</sub>	Chroma	Hue
1	0	0%	0%
2	0	0%	0%
3	0	0%	0%
4	0	0%	0%
5	0	0%	0%
6	0	0%	0%
7	0	0%	0%
8	0	0%	0%
9	0	0%	0%
10	0	0%	0%
11	0	0%	0%
12	0	0%	0%
13	0	0%	0%
14	0	0%	0%
15	0	0%	0%
16	0	0%	0%





## Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
135lx	34lx	15lx	8lx	5lx	4lx	3lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx
12,5fcd	3,1fcd	1,4fcd	0,8fcd	0,5fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd	0fcd	0fcd	0fcd

## Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
135	134	134	131	127	124	118	112	104	107	103	53	68	61	47	32	22	7	2	0
100%	100%	99%	97%	94%	92%	88%	83%	77%	79%	76%	39%	51%	45%	35%	24%	16%	5%	1%	0%

## Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
135	134	132	130	127	124	119	112	105	97	87	78	66	52	38	24	12	5	1	0
100%	99%	98%	96%	94%	92%	88%	83%	78%	72%	65%	58%	49%	39%	28%	18%	9%	4%	1%	0%

## Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
135	134	134	131	127	124	118	112	104	107	103	53	68	61	47	32	22	7	2	0
100%	100%	99%	97%	94%	92%	88%	83%	77%	79%	76%	39%	51%	45%	35%	24%	16%	5%	1%	0%

## Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
135	134	132	130	127	124	119	112	105	97	87	78	66	52	38	24	12	5	1	0
100%	99%	98%	96%	94%	92%	88%	83%	78%	72%	65%	58%	49%	39%	28%	18%	9%	4%	1%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
121,5°	164,9°	175,4°	77,2%	51,6%

**ISO candela diagram**




10%	13 cd
20%	27 cd
30%	40 cd
40%	54 cd
50%	67 cd
60%	81 cd
70%	94 cd
80%	108 cd
90%	121 cd

Conditions:

Number of c-planes: 16

Candela at center: 135 cd

**ISO lux diagram**



3%	40,4m lx
5%	67,4m lx
10%	0,135 lx
30%	0,404 lx
50%	0,674 lx

Conditions:

Number of c-planes: 16

Lux at center: 1,35 lx

*Lux distribution on a surface  
when lamp is mounted at 10  
meters from the surface.*

### Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X      Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	19,5	20,8	19,8	21,1	21,3	20,6	21,9	20,9	22,2	22,4
	3H	21,1	22,3	21,5	22,6	22,8	21,9	23,2	22,3	23,5	23,7
	4H	21,5	22,8	22,0	23,1	23,3	22,3	23,6	22,8	23,9	24,1
	6H	21,9	23,0	22,2	23,3	23,7	22,7	23,8	23,0	24,1	24,4
	8H	22,0	23,1	22,4	23,4	23,8	22,8	23,8	23,1	24,1	24,5
	12H	22,0	23,0	22,4	23,4	23,8	22,8	23,8	23,1	24,1	24,6
4H	2H	20,1	21,3	20,5	21,6	21,9	21,0	22,2	21,4	22,5	22,7
	3H	22,0	23,0	22,4	23,3	23,8	22,6	23,6	22,9	23,9	24,4
	4H	22,5	23,4	22,9	23,9	24,4	23,0	23,9	23,4	24,3	24,9
	6H	22,9	23,8	23,4	24,2	24,5	23,4	24,3	23,9	24,7	25,0
	8H	23,0	23,9	23,5	24,2	24,6	23,5	24,3	24,0	24,7	25,1
	12H	23,1	23,8	23,6	24,2	24,7	23,6	24,3	24,1	24,7	25,2
8H	4H	22,8	23,6	23,3	24,0	24,3	23,2	24,0	23,7	24,4	24,8
	6H	23,3	23,9	23,8	24,4	24,9	23,8	24,4	24,3	24,9	25,4
	8H	23,5	24,1	24,0	24,6	25,2	24,0	24,5	24,5	25,0	25,7
	12H	23,6	24,1	24,2	24,6	25,2	24,1	24,5	24,7	25,0	25,7
12H	4H	22,8	23,5	23,3	23,9	24,4	23,2	23,9	23,7	24,3	24,8
	6H	23,4	23,9	23,9	24,4	25,1	23,8	24,4	24,3	24,9	25,5
	8H	23,6	24,1	24,2	24,6	25,2	24,0	24,5	24,6	25,0	25,6
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,3 / -0,3					0,1 / -0,1				
S = 1.5H		0,6 / -0,6					0,3 / -0,4				
S = 2.0H		0,9 / -0,6					0,8 / -0,8				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 417 lm total luminous flux											

## Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	106	101	97	93	97	93	90	93	90	88	89	87	85	83
2	98	90	83	77	96	88	81	76	84	79	74	81	76	72	78	74	71	68
3	89	78	70	63	87	77	69	63	74	67	62	71	65	61	68	64	59	57
4	82	69	60	53	79	68	60	53	65	58	52	63	57	52	61	55	51	49
5	75	62	53	46	73	61	52	45	58	51	45	56	50	44	55	49	44	42
6	69	55	46	40	67	55	46	40	53	45	39	51	44	39	49	43	39	36
7	64	50	41	35	62	49	41	35	48	40	35	46	39	34	45	39	34	32
8	60	46	37	31	58	45	37	31	44	36	31	42	36	31	41	35	30	28
9	56	42	34	28	54	41	33	28	40	33	28	39	32	28	38	32	27	26
10	52	39	31	25	51	38	30	25	37	30	25	36	30	25	35	29	25	23

LAMPS (number of lamps)


Luminaire budgetary diagram



## Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
12,8 lm	37,0 lm	57,2 lm	70,3 lm	77,0 lm	67,5 lm	53,5 lm	31,7 lm	9,74 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,007 lm	0,000 lm	0,000 lm	0,000 lm	0,000 lm	0,000 lm	0,000 lm	0,000 lm	0,000 lm

### Warmup curve



### Warmup result

Warmup time:	27 min 3 sec
Warmup variation	-11,7%

### Warmup conditions

Stable period:	15 min
Stable change max:	2,0%
Minimum time:	15 min

### Color temperature change

CCT start	CCT change	CCT end
0 K	0 K	0 K

### Output change

Output start	Output change	Output end
467 lm	-50 lm	417 lm