Light efficiency:

36 Lumen/Watt

Light quality:


CRI: 0,0


Color temperature:

0 K

Output: 280 lm
Peak: 133 cd

Power: 7,7 W
PF: 1,0





CIE 1931
x: 0,119
y: 0,098


Product name:
Defiant-3_510mm_XXB_Lens-60°-Frosted

Item number:
NP/L3C/22C/0510/XXB/L6F


Date and time:
07.07.2020 14:49:19

Description:
Toleranzen:
Lumen +/-4%
Candela +/-2,5%
Colour Temp +/-35 K
CRI +/-0,7
Angular Resolution 1 Grad Step
Last Calibration 20.05.2020
Pruefer:
Peter Ulrich
Pruefort:
Lichtlabor
Gaustrasse 13
55411 Bingen am Rhein


Spectra




Power



Color details




CIE 1931




CIE 1931 ZOOM

TM30: 0,0



CRI: 0,0 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS: 0,0



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0,0	0,0	0,0	0,0	0,0	0,119	0,098	0,120	0,150	NaN

TM30 details


Rf 0,0

Fidelity index Rf


Rg 0,0

Gammut index Rg


		Graphic shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	0	0%	0%
2	0	0%	0%
3	0	0%	0%
4	0	0%	0%
5	0	0%	0%
6	0	0%	0%
7	0	0%	0%
8	0	0%	0%
9	0	0%	0%
10	0	0%	0%
11	0	0%	0%
12	0	0%	0%
13	0	0%	0%
14	0	0%	0%
15	0	0%	0%
16	0	0%	0%















Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
129lx	32lx	14lx	8lx	5lx	4lx	3lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx
12fcd	3fcd	1,3fcd	0,7fcd	0,5fcd	0,3fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
129	129	130	132	133	127	99	60	34	22	17	14	15	20	18	13	8	5	2	0
100%	100%	101%	102%	103%	98%	77%	46%	27%	17%	13%	11%	12%	15%	14%	10%	6%	4%	2%	0%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
129	129	128	126	123	120	118	113	109	103	94	82	65	47	32	20	11	5	1	0
100%	100%	99%	98%	96%	93%	91%	88%	84%	80%	73%	63%	50%	37%	25%	15%	8%	4%	1%	0%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
129	129	130	132	133	127	99	60	34	22	17	14	15	20	18	13	8	5	2	0
100%	100%	101%	102%	103%	98%	77%	46%	27%	17%	13%	11%	12%	15%	14%	10%	6%	4%	2%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
129	129	128	126	123	120	118	113	109	103	94	82	65	47	32	20	11	5	1	0
100%	100%	99%	98%	96%	93%	91%	88%	84%	80%	73%	63%	50%	37%	25%	15%	8%	4%	1%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
85,9°	**147,9°**	**175,8°**	**83,7%**	**67,1%**

ISO candela diagram




10%	13 cd
20%	26 cd
30%	39 cd
40%	52 cd
50%	64 cd
60%	77 cd
70%	90 cd
80%	103 cd
90%	116 cd

Conditions:

Number of c-planes: 16

Candela at center: 129 cd

ISO lux diagram



Mounting height: 10 meters (33 feet)

3%	38,7m lx
5%	64,4m lx
10%	0,129 lx
30%	0,387 lx
50%	0,644 lx

Conditions:

Number of c-planes: 16

Lux at center: 1,29 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.


Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	12,2	13,3	12,4	13,6	13,8	19,7	20,8	19,9	21,1	21,3
	3H	14,4	15,5	14,8	15,8	16,0	20,8	21,9	21,2	22,2	22,4
	4H	15,1	16,2	15,5	16,5	16,7	21,3	22,3	21,7	22,6	22,8
	6H	15,7	16,7	16,0	16,9	17,3	21,7	22,6	22,0	22,9	23,2
	8H	15,8	16,7	16,2	17,1	17,5	21,8	22,7	22,1	23,0	23,4
	12H	15,9	16,8	16,3	17,1	17,6	21,8	22,7	22,2	23,0	23,5
4H	2H	12,9	13,9	13,3	14,2	14,4	19,5	20,6	19,9	20,8	21,1
	3H	15,4	16,2	15,7	16,6	17,0	20,8	21,7	21,2	22,0	22,5
	4H	16,2	17,0	16,6	17,4	17,9	21,3	22,1	21,7	22,5	23,0
	6H	16,8	17,6	17,3	18,0	18,3	21,7	22,5	22,2	22,8	23,2
	8H	17,0	17,7	17,5	18,1	18,5	21,9	22,6	22,4	22,9	23,3
	12H	17,1	17,7	17,6	18,1	18,6	22,0	22,6	22,5	23,0	23,5
8H	4H	16,6	17,3	17,1	17,7	18,0	21,3	22,0	21,8	22,3	22,7
	6H	17,4	17,9	17,9	18,4	18,9	21,8	22,3	22,3	22,8	23,3
	8H	17,7	18,1	18,2	18,7	19,3	22,0	22,5	22,6	23,0	23,7
	12H	17,9	18,3	18,5	18,8	19,4	22,2	22,6	22,8	23,1	23,7
12H	4H	16,6	17,2	17,1	17,6	18,1	21,2	21,8	21,7	22,2	22,7
	6H	17,5	18,0	18,0	18,5	19,1	21,8	22,3	22,3	22,8	23,4
	8H	17,8	18,2	18,4	18,7	19,3	22,1	22,4	22,6	22,9	23,6
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,5 / -0,3					0,5 / -0,7				
S = 1.5H		1,0 / -0,6					1,4 / -1,7				
S = 2.0H		1,6 / -0,6					2,5 / -2,6				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 280 lm total luminous flux											

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)				Room Values are expressed as percentage of Lumens delivered to the task surface													
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	109	105	101	98	107	103	99	96	98	95	93	94	92	89	90	88	86	84
2	101	94	87	82	98	91	86	81	88	83	79	84	80	77	81	78	75	73
3	93	84	77	71	91	82	75	70	79	73	68	76	71	67	73	69	66	64
4	86	76	68	62	84	74	67	61	71	65	60	69	63	59	67	62	58	56
5	80	69	60	54	78	67	60	54	65	58	53	63	57	53	61	56	52	50
6	75	63	54	49	73	61	54	48	60	53	48	58	52	47	56	51	47	45
7	70	57	49	44	68	56	49	43	55	48	43	53	47	43	52	46	42	40
8	65	53	45	40	64	52	45	39	51	44	39	49	43	39	48	42	38	37
9	61	49	41	36	60	48	41	36	47	40	36	46	40	35	45	39	35	33
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	36	32	31

Luminaire budgetary diagram




Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
12,3 lm	36,5 lm	57,7 lm	58,4 lm	41,8 lm	27,5 lm	20,1 lm	13,7 lm	5,81 lm

90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
1,50 lm	1,10 lm	0,861 lm	0,762 lm	0,657 lm	0,533 lm	0,393 lm	0,241 lm	0,081 lm

Warmup curve



Warmup result

Warmup time:	**Lamp stabilized in 15 min 2 sec**
Warmup variation	**-0,5%**

Warmup conditions

Stable period:	**15 min**
Stable change max:	**2,0%**
Minimum time:	**15 min**

Color temperature change

CCT start	CCT change	CCT end
0 K	0 K	0 K

Output change

Output start	Output change	Output end
281 lm	-1 lm	280 lm