Light efficiency:

43 Lumen/Watt

Light quality:


CRI: 0,0


Color temperature:

0 K

Output: 410 lm
Peak: 141 cd

Power: 9,6 W
PF: 1,0





CIE 1931
x: 0,683
y: 0,301


Product name:
Defiant-3_510mm_XXR_Cover-Square-Frosted

Item number:
NP/L3C/22C/0510/XXR/CSF


Date and time:
30.06.2020 13:00:22

Description:
Toleranzen:
Lumen +/-4%
Candela +/-2,5%
Colour Temp +/-35 K
CRI +/-0,7
Angular Resolution 1 Grad Step
Last Calibration 20.05.2020
Pruefer:
Peter Ulrich
Pruefort:
Lichtlabor
Gaustrasse 13
55411 Bingen am Rhein


Spectra



Power



Color details




CIE 1931




CIE 1931 ZOOM

TM30: 0,0



CRI: 0,0 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

CQS: 0,0



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0,0	0,0	0,0	0,0	0,0	0,683	0,301	0,521	0,344	NaN

TM30 details


Rf 0,0

Fidelity index Rf


Rg 0,0

Gammut index Rg


		Graphic shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	0	0%	0%
2	0	0%	0%
3	0	0%	0%
4	0	0%	0%
5	0	0%	0%
6	0	0%	0%
7	0	0%	0%
8	0	0%	0%
9	0	0%	0%
10	0	0%	0%
11	0	0%	0%
12	0	0%	0%
13	0	0%	0%
14	0	0%	0%
15	0	0%	0%
16	0	0%	0%















Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
140lx	35lx	16lx	9lx	6lx	4lx	3lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx
13fcd	3,3fcd	1,4fcd	0,8fcd	0,5fcd	0,4fcd	0,3fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
140	140	138	134	129	123	115	106	96	86	76	67	60	53	46	39	30	23	8	0
100%	100%	98%	96%	92%	88%	82%	75%	68%	61%	54%	48%	43%	38%	33%	28%	21%	16%	6%	0%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
140	139	138	135	131	126	119	110	100	89	76	63	50	38	27	18	12	6	2	0
100%	99%	98%	97%	94%	90%	85%	79%	72%	64%	54%	45%	36%	27%	20%	13%	8%	4%	1%	0%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
140	140	138	134	129	123	115	106	96	86	76	67	60	53	46	39	30	23	8	0
100%	100%	98%	96%	92%	88%	82%	75%	68%	61%	54%	48%	43%	38%	33%	28%	21%	16%	6%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
140	139	138	135	131	126	119	110	100	89	76	63	50	38	27	18	12	6	2	0
100%	99%	98%	97%	94%	90%	85%	79%	72%	64%	54%	45%	36%	27%	20%	13%	8%	4%	1%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
105,2°	**171,6°**	**218°**	**73,4%**	**51,2%**

ISO candela diagram




10%	14 cd
20%	28 cd
30%	42 cd
40%	56 cd
50%	70 cd
60%	84 cd
70%	98 cd
80%	112 cd
90%	126 cd

Conditions:

Number of c-planes: 16

Candela at center: 140 cd

ISO lux diagram



Mounting height: 10 meters (33 feet)

3%	42,0m lx
5%	70,0m lx
10%	0,140 lx
30%	0,420 lx
50%	0,700 lx

Conditions:

Number of c-planes: 16

Lux at center: 1,40 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.


Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18,8	20,0	19,0	20,3	20,5	19,3	20,6	19,6	20,9	21,1
	3H	20,4	21,7	20,8	22,0	22,2	20,4	21,7	20,9	22,0	22,2
	4H	21,2	22,4	21,6	22,7	22,9	20,9	22,2	21,3	22,4	22,7
	6H	21,9	23,0	22,2	23,3	23,7	21,4	22,4	21,7	22,7	23,1
	8H	22,2	23,2	22,5	23,6	24,0	21,5	22,5	21,8	22,8	23,2
	12H	22,4	23,4	22,8	23,8	24,2	21,5	22,6	21,9	22,9	23,4
4H	2H	19,3	20,5	19,7	20,8	21,1	19,7	21,0	20,1	21,2	21,5
	3H	21,3	22,3	21,6	22,6	23,1	21,2	22,2	21,6	22,6	23,0
	4H	22,1	23,1	22,6	23,5	24,0	21,7	22,7	22,2	23,1	23,6
	6H	23,0	23,9	23,5	24,2	24,6	22,2	23,1	22,7	23,5	23,9
	8H	23,3	24,2	23,8	24,5	24,9	22,4	23,2	22,9	23,6	24,0
	12H	23,6	24,3	24,1	24,8	25,2	22,5	23,2	23,0	23,7	24,1
8H	4H	22,4	23,3	22,9	23,6	24,0	22,0	22,9	22,6	23,3	23,6
	6H	23,5	24,1	24,0	24,6	25,1	22,7	23,4	23,2	23,8	24,4
	8H	24,0	24,5	24,5	25,1	25,7	23,0	23,6	23,5	24,1	24,7
	12H	24,4	24,9	25,0	25,4	26,0	23,2	23,7	23,8	24,2	24,8
12H	4H	22,4	23,1	22,9	23,6	24,0	22,1	22,8	22,6	23,2	23,7
	6H	23,6	24,1	24,1	24,7	25,3	22,8	23,4	23,4	23,9	24,6
	8H	24,1	24,6	24,7	25,1	25,7	23,2	23,7	23,8	24,2	24,8
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,1 / -0,1				
S = 1.5H		0,1 / -0,2					0,3 / -0,3				
S = 2.0H		0,3 / -0,3					0,7 / -0,7				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 410 lm total luminous flux											

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)				Room Values are expressed as percentage of Lumens delivered to the task surface													
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	96
1	107	102	97	93	104	99	95	91	94	91	87	90	87	84	85	83	81	79
2	97	88	81	75	94	86	80	74	82	77	72	78	74	70	75	71	68	65
3	88	78	69	63	86	76	68	62	72	66	60	69	63	59	66	61	57	55
4	81	69	60	53	78	67	59	53	64	57	51	62	55	50	59	54	49	47
5	75	62	52	46	72	60	52	45	58	50	45	55	49	44	53	47	43	41
6	69	55	46	40	67	54	46	40	52	45	39	50	43	38	48	42	38	36
7	64	50	42	35	62	49	41	35	48	40	35	46	39	34	44	38	34	32
8	60	46	37	32	58	45	37	31	44	36	31	42	35	31	41	35	30	28
9	56	42	34	28	54	42	34	28	40	33	28	39	32	28	38	32	27	25
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23

Luminaire budgetary diagram




Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
13,3 lm	38,0 lm	57,2 lm	67,4 lm	67,0 lm	58,1 lm	45,4 lm	31,5 lm	17,6 lm

90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
5,49 lm	3,67 lm	1,61 lm	1,08 lm	0,937 lm	0,760 lm	0,560 lm	0,343 lm	0,115 lm

Warmup curve



Warmup result

Warmup time:	**Lamp stabilized in 20 min 41 sec**
Warmup variation	**-5,1%**

Warmup conditions

Stable period:	**15 min**
Stable change max:	**2,0%**
Minimum time:	**15 min**

Color temperature change

CCT start	CCT change	CCT end
0 K	0 K	0 K

Output change

Output start	Output change	Output end
436 lm	-26 lm	410 lm