Light efficiency:

124 Lumen/Watt

Light quality:


CRI: 94,7


Color temperature:

2700 K

Output: 298 lm
Peak: 98,4 cd

Power: 2,4 W
PF: 1,0





Product name:
Sta-Maria-6_510mm_927_Cover-Square-Transparent


Item number:
NP/L1C/01E/0510/927/CST

Date and time:
27.06.2022 11:25:29


Description:
Tolerances:
Lumen +/-4%
Candela +/-2,5%
Colour Temp +/-35 Kelvin
CRI +/-0,7
Angular Resolution: 1 Degree Step
Last Calibration 20-09-2021
Tester: Peter Ulrich
Test Site: Lichtlabor
Gaustrasse 13
55411 Bingen am Rhein

CIE 1931
x: 0,460
y: 0,411


Spectra




Power




Color details






TM30: 92,3



CRI: 94,7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95,5	97,7	98,2	95,4	95,1	96,8	93,1	85,4	68,1	93,5	96,6	82,2	96,3	98,1	91,6


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92,2	93,7	92,0	94,1	94,8	96,0	94,5	98,2	94,3	90,3	89,1	90,0	92,0	88,6	92,9	86,3

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
89,7	95,2	89,1	89,0	92,4	93,5	91,4	92,5	97,2	94,4	94,1	93,6	93,4	89,2	89,3

CQS: 91,7



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2700 K	94,7	68,1	92,3	99,7	91,7	0,460	0,411	0,263	0,352	-0,0006

TM30 details


Rf 92,3


Fidelity index Rf


Rg 99,7


Gammut index Rg


		Graphic shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	92	-4%	0%
2	94	-3%	2%
3	92	-1%	4%
4	94	-2%	1%
5	95	-1%	2%
6	96	2%	1%
7	94	-2%	-1%
8	98	0%	0%
9	94	-1%	3%
10	90	0%	6%
11	89	2%	8%
12	90	5%	1%
13	92	3%	-5%
14	89	4%	-8%
15	93	-2%	-3%
16	86	-2%	-11%















Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
98lx	25lx	11lx	6lx	4lx	3lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx
9,1fcd	2,3fcd	1fcd	0,6fcd	0,4fcd	0,3fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
98,3	98,1	97,0	95,1	92,3	89,1	85,3	80,2	74,6	75,1	72,8	40,1	43,3	42,1	32,4	20,9	13,2	5,0	0,4	0,0
100%	100%	99%	97%	94%	91%	87%	82%	76%	76%	74%	41%	44%	43%	33%	21%	13%	5%	0%	0%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
98,3	97,9	97,0	95,1	92,8	89,6	85,8	81,5	75,8	69,6	62,4	54,9	46,6	36,9	27,1	16,9	8,6	3,3	0,5	0,0
100%	100%	99%	97%	94%	91%	87%	83%	77%	71%	63%	56%	47%	38%	28%	17%	9%	3%	1%	0%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
98,3	98,1	97,0	95,1	92,3	89,1	85,3	80,2	74,6	75,1	72,8	40,1	43,3	42,1	32,4	20,9	13,2	5,0	0,4	0,0
100%	100%	99%	97%	94%	91%	87%	82%	76%	76%	74%	41%	44%	43%	33%	21%	13%	5%	0%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
98,3	97,9	97,0	95,1	92,8	89,6	85,8	81,5	75,8	69,6	62,4	54,9	46,6	36,9	27,1	16,9	8,6	3,3	0,5	0,0
100%	100%	99%	97%	94%	91%	87%	83%	77%	71%	63%	56%	47%	38%	28%	17%	9%	3%	1%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
115,1°	**165,1°**	**174,3°**	**77,6%**	**52,1%**

ISO candela diagram




10%	10 cd
20%	20 cd
30%	29 cd
40%	39 cd
50%	49 cd
60%	59 cd
70%	69 cd
80%	79 cd
90%	88 cd

Conditions:

Number of c-planes: 16

Candela at center: 98 cd

ISO lux diagram



Mounting height: 10 meters (33 feet)

3%	29,5m lx
5%	49,1m lx
10%	98,3m lx
30%	0,295 lx
50%	0,491 lx

Conditions:

Number of c-planes: 16

Lux at center: 0,983 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.


Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18,2	19,4	18,4	19,7	20,0	19,4	20,6	19,6	21,0	21,2
	3H	19,7	21,0	20,1	21,3	21,5	20,7	22,0	21,1	22,2	22,4
	4H	20,1	21,4	20,6	21,6	21,9	21,1	22,3	21,5	22,6	22,9
	6H	20,5	21,6	20,8	21,8	22,2	21,5	22,5	21,8	22,8	23,2
	8H	20,6	21,6	20,9	21,9	22,3	21,5	22,6	21,9	22,9	23,3
	12H	20,6	21,6	21,0	21,9	22,4	21,5	22,5	21,9	22,9	23,3
4H	2H	18,7	20,0	19,1	20,2	20,5	19,7	20,9	20,1	21,2	21,4
	3H	20,6	21,6	21,0	21,9	22,4	21,3	22,3	21,7	22,6	23,1
	4H	21,1	22,0	21,5	22,4	23,0	21,7	22,6	22,2	23,1	23,6
	6H	21,4	22,3	21,9	22,7	23,0	22,1	23,0	22,6	23,4	23,7
	8H	21,5	22,4	22,0	22,7	23,1	22,2	23,0	22,7	23,4	23,8
	12H	21,6	22,3	22,1	22,7	23,2	22,3	23,0	22,8	23,4	23,9
8H	4H	21,3	22,2	21,8	22,5	22,9	21,9	22,7	22,4	23,1	23,5
	6H	21,8	22,4	22,3	22,9	23,4	22,5	23,1	23,0	23,5	24,1
	8H	22,0	22,6	22,5	23,1	23,7	22,7	23,2	23,2	23,7	24,4
	12H	22,2	22,6	22,7	23,1	23,7	22,8	23,2	23,3	23,7	24,3
12H	4H	21,3	22,0	21,8	22,4	22,9	21,9	22,6	22,4	23,0	23,5
	6H	21,9	22,4	22,4	22,9	23,6	22,5	23,0	23,0	23,6	24,2
	8H	22,1	22,5	22,7	23,0	23,6	22,7	23,2	23,3	23,7	24,3
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,4 / -0,3					0,1 / -0,1				
S = 1.5H		0,6 / -0,9					0,3 / -0,5				
S = 2.0H		1,0 / -0,7					0,8 / -0,9				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 298 lm total luminous flux											

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)				Room Values are expressed as percentage of Lumens delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	99
1	108	103	99	95	106	101	97	93	97	93	90	93	90	88	89	87	85	83
2	98	90	83	77	96	88	82	76	84	79	74	81	76	72	78	74	71	69
3	89	79	70	64	87	77	69	63	74	67	62	71	66	61	69	64	60	57
4	82	70	61	54	79	68	60	53	66	58	53	63	57	52	61	56	51	49
5	75	62	53	46	73	61	52	46	59	51	45	57	50	45	55	49	44	42
6	69	56	47	40	67	55	46	40	53	45	40	51	44	39	50	44	39	37
7	64	51	42	35	62	50	41	35	48	40	35	47	40	35	45	39	34	32
8	60	46	37	31	58	45	37	31	44	36	31	43	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	25	37	30	25	36	30	25	35	29	25	23

Luminaire budgetary diagram




Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
9,33 lm	26,9 lm	41,3 lm	50,7 lm	54,9 lm	48,2 lm	36,8 lm	21,7 lm	6,58 lm

90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,632 lm	0,206 lm	0,164 lm	0,148 lm	0,128 lm	0,104 lm	0,077 lm	0,047 lm	0,016 lm

Warmup curve



Warmup result

Warmup time:	**Lamp stabilized in 15 min 2 sec**
Warmup variation	**-1,1%**

Warmup conditions

Stable period:	**15 min**
Stable change max:	**2,0%**
Minimum time:	**15 min**

Color temperature change

CCT start	CCT change	CCT end
2703 K	-3 K	2700 K

Output change

Output start	Output change	Output end
302 lm	-4 lm	298 lm